

MICRODROP DISPENSING APPARATUS

Background of the Invention

The invention relates generally to apparatus for depositing small droplets of liquid. More particularly, the invention has application to the type of apparatus discussed in, for example, in PCT publication WO 98/45205, assigned to the Packard Instrument Company, which describes equipment capable of aspirating a liquid and dispensing it in droplets having a volume in the range of 5 to 500 picoliters. Such small droplets are ejected from the tip of a capillary by applying a voltage pulse to a piezoelectric transducer surrounding the capillary, producing a force sufficient to dispense one or a series of small droplets having a diameter similar to that of the opening of the capillary. Although there are various end uses for such equipment, it is particularly useful in connection with microscale chemical and biological analysis. The published PCT patent application suggests means for cleaning the tip of such capillaries which may easily become clogged. The present invention solves another problem to which the equipment may be subject, namely damage to the capillaries during the use of the apparatus. In addition, the invention has application to determining the position of a solid or a liquid surface.

In a typical operation, the tip of a capillary is moved into contact with liquid in a container and the liquid is aspirated, after which the capillary is moved to another location, where the liquid is dispensed in one or more droplets as desired. Then the capillary may be moved to another location, where additional droplets are dispensed or to a wash station where the capillary is cleaned before being used to aspirate and dispense another sample of liquid. It is also possible to maintain the capillary in one location and to move the containers or the surfaces which receive the liquid droplets under the capillary. Generally, such operations require the capillary to be moved vertically downward so that the tip is brought close to the bottom of the sample container or surface and then moved upwardly so that the sample container or surface can be exchanged for another. The capillaries are commonly made of glass and can

easily be broken if they contact a sample container or surface. This not only interrupts the process being performed, but it is costly to replace the capillaries and the associated piezoelectric transducers. The breakage problem is multiplied when the number of capillaries is increased or the sizes of the associated sample containers and surfaces are decreased relative to the size of the capillaries.

For most practical applications of this technology the process must be automated. It can be appreciated that if the tip of a capillary is brought to within about 0.4 mm of the bottom of a sample container or another surface, that positioning the tip is difficult to do manually and damage to the tips could easily occur. If multiple capillaries are used, the damage potentially could be very great. Small errors in the positioning of the sample containers or droplet receiving surfaces can cause a capillary to unintentionally contact the wall of the sample container or the surface and to break. This may result from errors in programming, but even if the operator of such equipment has accurately programmed the movement of the capillaries for the necessary movements in three dimensions, it is still possible for errors in positioning of the sample containers or surfaces to lead to expensive damage to the capillaries.

Frequently, the microdispensing apparatus will be used to aspirate samples from a microplate having an array of small wells which hold liquid. A common size is a 96 well plate, measuring about 80 by 120 mm and having round sample wells having a diameter of about 6.5 mm. However, more recently plates having 384 and 1536 wells have become available. These have the advantage of further reducing the volume of the liquids needed to fill a well. However, these newer plates have the disadvantage of having sample wells which are much smaller than those in the 96 well plates. For example, the 384 well plate will have square wells with each side only 3.6 mm, while a 1536 well plate will have square wells with each side less than 1.5 mm. When one considers that the outside dimension of a typical capillary is only about 1 mm, it is evident that there is very little room for error in programming the three-dimensional movement of the capillaries or in positioning of the sample containers or surfaces. Therefore, the present inventors have addressed the problem of preventing or at least minimizing the possibility of contact between the capillaries and the sample containers or surfaces, so that the microdrop dispensing equipment can be used

commercially with little or no downtime resulting from damage to the delicate capillaries. Their solution to the problem is described below in detail. In one broad aspect their invention involves using the capillary with its piezoelectric transducer to detect contact with the solid surfaces, such as sample wells or droplet receiving surfaces and taking corrective action to prevent or at least to limit damage to the capillaries. The invention may also be applied to detect the location of a solid or a liquid surface.

Summary of the Invention

In one aspect, the invention is a method of detecting when a capillary for dispensing liquids by action of a piezoelectric transducer comes in contact with a surface. The electrical voltage created by the piezoelectric transducer in response to such contact is detected and corrective action can be taken to avoid breakage of the capillary. In a related aspect, the electrical voltage change created when the capillary touches a surface is used to establish the position of a surface, either liquid or solid surface.

In another embodiment, the invention is a method of detecting when a capillary for dispensing liquids by action of a piezoelectric transducer comes into contact with a surface, in which the piezoelectric transducer surrounding the capillary is driven with a low oscillating voltage at its resonant frequency to establish a signal corresponding to the capillary and an inverted signal is created in phase with the signal of the capillary as a reference. When the capillary contacts a surface, the phase shift of the capillary signal relative to the reference signal is detected, and triggers corrective action. In a related aspect, the phase shift just described is used to establish the position of a surface, either liquid or solid. Preferably, the phase shift can be readily detected by summing the voltage potentials and detecting the voltage change.

In another aspect, the invention is an apparatus for dispensing microdrops of liquid by the action of a piezoelectric transducer in which the transducer is used to detect the contact with a solid surface by the capillary used to dispense the microdrops and to prevent damage to the capillary, or alternatively to establish the position of a surface, either liquid or solid. In one embodiment, the voltage produced when contact

is made with a surface is made is used to detect contact. In another embodiment, the capillary is driven at its resonant frequency to establish a capillary signal, which is compared with an inverted signal as a reference and the phase shift between the signals resulting from contact of the capillary is detected. Preferably, the phase shift is detected by summing the voltage potentials and detecting the voltage change.

In still another aspect, the invention is the improvement in a capillary equipped with a piezoelectric transducer for expelling small droplets of liquid from the tip of the capillary when a voltage is applied to the piezoelectric transducer, and in which the transducer is used to detect contact with a surface. In one embodiment, the contact with a surface creates a voltage from the force applied to the transducer by contact with a surface. In another embodiment, the capillary is driven at its resonant frequency to establish a capillary signal, which is compared with an inverted reference signal and the phase shift between the signals produced by contact is detected. Corrective action can be taken typically by stopping movement of the capillary to prevent damage to the capillary. Alternatively, the technique can be used to establish the position of a solid or liquid surface.

Brief Description of the Drawings

Figure 1 is a graph of the voltage generated when a capillary hits a solid surface in the vertical (Z) direction.

Figure 2 is a graph of the voltage generated when a capillary hits a solid surface in the horizontal (X-Y) plane.

Figure 3 is a graph of the voltage generated in a second type of contact of a capillary with a solid surface in the horizontal (X-Y) plane.

Figure 4 is a graph of the unfiltered voltage generated by the excursion when the capillary contacts a solid surface plus an overlay of the amplified voltage produced by the capillary contact. The random noise has not been filtered.

Figure 5 is a block diagram of the control systems used to operate the micro dispensing apparatus and to prevent breakage of the capillary.

Description of the Preferred Embodiments

Microdrop Dispensing Apparatus

As mentioned above, the invention has particular relevance to apparatus used to dispense very small drops of liquid, such as those described in detail in PCT publication WO 98/45205 by the Packard Instrument Company. The microdrop dispensing systems will be described briefly here. For more details, reference may be made to the published patent application. The invention is not limited to the specific equipment described there, but may be applied to other equipment employing piezoelectric transducers to dispense drops of liquid.

Two types of liquid dispensing systems are described in WO 98/45205, both of which employ a capillary tube terminating in a smaller dispensing tip having an internal diameter of about 25 to 100 microns and capable of dispensing drops of liquid having a volume of about 5 to 500 picoliters. By surrounding the capillary tube with a piezoelectric transducer, it is possible to apply a voltage pulse, e.g. between about 40 and 300 volts to the transducer, which is mechanically deformed, compressing the capillary and expelling a drop of liquid. When the voltage is applied for a very short time a single drop is expelled. If the voltage is applied with a frequency up to about 1,000 Hz, a series of droplets can be expelled to provide the volume of liquid which one wishes to dispense.

The published patent application describes generally the operation of a robotic system which positions the microdrop dispensing capillary tip over a sample liquid in its container, such a microplate shown in Figure 5 of the application. The tip is moved until it makes contact with the surface of the liquid in the container, which contact may be sensed by a capacitive liquid level sensing system, so that the movement of the capillary is stopped and the liquid is aspirated into the capillary. Then, the capillary can be moved to another location and the aspirated liquid dispensed as desired. The published patent application also describes an optical method of positioning the capillary tip within each well of a microplate.

While the description herein is principally concerned with apparatus in which the capillary is moved from one location to aspirate liquid and to a second location to dispense microdrops of the liquid, it should be understood that the opposite arrangement is feasible and may be preferred for large scale commercial use. That is,

in the simplest form, a single capillary is mounted on a moveable support and moved horizontally in the X-Y plane and vertically in the Z direction into a first location, such as the well of a microplate to aspirate a liquid and then to a second location, such as a planar surface on which microdrops of the liquid are dispensed. Thus, the

5 capillary moves while the liquid containers e.g. a sample well or the surface which receives the microdrops are stationary. Alternatively, the capillary could be stationary and the container and surface could be moved under the capillary, which is moved only in the vertical direction (Z). Such an alternative arrangement may be desirable particularly when multiple capillaries are mounted in an array and it is more

10 convenient to move the containers, sample plates and surfaces than to move the array of capillaries. It is of course possible to use an apparatus capable of moving each of the capillaries, the containers, the sample plates, and the surfaces independently for maximum flexibility of operation. Each embodiment is subject to the problems discussed above, since no matter which is used, movement may bring a capillary into

15 contact with a container or a surface, resulting in damage to the capillary.

In practice, it is not desirable to carry out such movements manually, using visual observation by the operator. To assure accuracy in repetitive steps of aspirating and dispensing liquids, computer control of the movements of the capillaries generally will be provided. The operator of the apparatus will instruct the computer to carry out

20 a series of movements intended to transfer liquid from a container and to dispense it into a second container or onto a surface such as a glass slide. For example, a capillary could be instructed to move to a first well containing liquid, aspirate a predetermined amount of the liquid, move to a predetermined location over a glass slide, and dispense a single drop of the liquid there, then move to other positions on

25 the same slide and dispense additional drops of liquid. After dispensing the desired amount of liquid, the capillary tip could be instructed to move to another location where it would be washed before the cycle is repeated. It will be appreciated that such a sequence of movements will take place in three dimensions, usually called X and Y defining the position in a horizontal plane and Z defining the position in the

30 vertical direction. Since the capillaries are very small, one can appreciate that they can be easily damaged if, during their travels in the X, Y and Z directions, they come

in contact with an obstacle, such as the well of a microplate or the surface of a glass slide. While it might be thought that the computer control could eliminate concern over such contacts, errors can occur leading to damage of the capillaries. These errors are generally of two types, the first, errors in programming of the computer control and the second, errors in positioning of the containers or the slides. The present inventors cannot prevent errors made by others, but they have developed a method for limiting or preventing the damage to capillaries which could otherwise occur.

The nature of the problem can be understood more easily when the dimensions of the capillary and the associated containers and surfaces and the distance between them are considered. The usual capillary has an internal diameter of about 300-800 microns and an external diameter of about 500-1,000 microns (0.5-1 mm). At the tip the capillary is reduced to an external diameter of about 100 microns and the dispensed droplets are even smaller. The 0.5-1.0 mm o.d. capillary will be inserted into the well of a microplate which has a diameter of no more than 6 mm and, often is as small as 2.6 mm square, sometimes with a 1,536-well microplate a well of about 1.5 mm square. The capillary tip may approach the bottom of the well within about 0.4 mm or 400 microns, or a similar distance from a glass slide on which it is to deposit a single drop. There is very little room for error in positioning the capillary and experience has shown that damage to the capillary is frequent enough to present a significant problem. Since the capillaries are very small and generally made of glass, very little force is required to break them. Thus, any contact between a capillary and any solid surface which could result in breakage must be detected quickly and corrective action taken at once.

While the above discussion considered the movement of a single capillary, when the microdrop dispensing method is applied on a large scale commercially, it is probable that many dispensing capillaries will be in operation simultaneously. For example, four up to a number equal to the number of containers from which liquid is to be aspirated. Therefore, potentially all of the many capillaries could be broken at the same time by a positioning error. Since each one is expensive, breaking many at one time must be prevented, as is possible with the present invention.

Detecting and Preventing Damage to Capillary Tips

Each capillary dispenses one or more drops when a piezoelectric transducer surrounding the capillary is activated by applying a brief voltage pulse, thereby compressing the capillary tube and expelling a drop for each pulse. The piezoelectric transducer can operate in a reverse manner, that is, it can create an electrical voltage if it is mechanically strained, a principle which is used for applications such as record players, cigarette lighters, igniters on barbecue grills and some microphones and speakers. The voltage produced by a piezoelectric transducer is related to the force applied to the transducer. In the present invention, the voltages generated and detected are generally quite small compared to the voltage used to compress a capillary tube and expel a liquid droplet, e.g., about 40 to 300 volts. Thus, while it might be anticipated that a capillary with a piezoelectric transducer could produce a voltage if the tip contacts a solid surface, it is not evident that the voltage could be distinguished from the random "noise" resulting from unrelated sources, so that it can be used to prevent breaking the tip, or to establish the position of a surface. The present inventors have found that to be possible, with the methods and apparatus to be described.

When the piezoelectric transducer is distorted mechanically so as to compress the capillary and dispense a liquid droplet, a relatively high voltage is used, as previously discussed. In contrast, when a capillary touches a solid surface during operation of the microdrop dispensing apparatus, a very small voltage of at least 10 millivolts (0.01 volt) is typically produced. At the same time, the capillary is constantly producing "noise", that is, voltage produced by the transducer from mechanical forces introduced by the movement of the capillary, the driving motors, external vibrations, and the like. Thus, if one measures the voltage being produced by the piezoelectric transducer while it is not dispensing droplets, it is found that an irregular random voltage is always being produced, typically of a similar order of magnitude as the voltage produced by contact with a surface. Such noise would not ordinarily be of concern and would be small enough in size as to have no significant effect on the dispensing of droplets. However, it is of a magnitude which can mask the voltage produced by contact of the capillary with a solid surface, especially if the

contact is slow, as it often is when contact occurs in the X-Y (horizontal) plane. Vertical contact in the Z direction often produces a more pronounced reaction. Examples of such contacts between a capillary and the wall of a container and between the tip of the capillary in the horizontal plane and a solid surface in the Z direction are shown in the Figures.

In Figure 1, a "hard" contact was made between a capillary and a solid surface in the Z (vertical) direction. The reference voltage is shown as a baseline bias voltage of two volts. When the capillary touches a surface a voltage change is produced (A1) from the strain in the piezoelectric transducer. The actual voltage has been amplified to show the variation from the baseline bias voltage of 2 volts.

A2 shows the voltage of about 4.5-5 volts used to establish a baseline for determining whether contact has occurred. When the voltage rise caused by the contact of a capillary reaches the switching threshold, the switching voltage is dropped to zero, causing the motor control module (see Fig. 5) to stop movement of the capillary to prevent breakage. The corrective action took place within 2 milliseconds after the voltage increase began, as shown by the voltage drop from 4.5-5 volts to zero as the controlling switch is opened.

Figure 2 illustrates the result of a capillary moving horizontally at 7.5 inches/second (190 mm/sec) coming into contact with the wall of a cell in a sample plate. As in Figure 1, the reference voltage has been shown as a nominal bias of two volts. When the capillary touched the cell wall, a voltage change was produced and detected in about one millisecond, as can be seen on the horizontal scale, triggering corrective action. In this instance, the voltage excursion was negative, rather than positive, as in Figure 1. Either negative or positive excursions may occur, depending on the direction of the strain on the piezoelectric transducer.

In Figure 3, a "soft" contact was made between a capillary moving at 7.5 inches/second (190 mm/sec) and a solid surface in the X-Y plane. The voltage excursion was slower than in Figure 2, but the result was similar. In about 7 milliseconds, the voltage excursion in A1 was detected and corrective action taken, as shown by the drop to zero voltage from the switching circuit (A2).

Figure 4 shows the “raw” voltage (A1) associated with a capillary when it is being moved, but not dispensing droplets. The scale for this data is 50 millivolts per division, indicating that the random noise is typically less than ± 50 millivolts. The actual voltage produced when a capillary contacts a solid surface is also small, in this Figure up to about 75 millivolts. The relatively small voltage excursion is amplified to provide a signal which is detected, as shown in the previous figures. This Figure illustrates the relationship between the actual voltage and the amplified signal. The “noise” is distributed uniformly about zero voltage and is filtered out. Only the excursion caused by contact of a capillary with a solid surface is amplified (A2).

Figure 5 is a block diagram illustrating the controls used to position the capillaries. The “tip detector” system receives the voltage being generated by a capillary, distinguishes between “noise” and a voltage generated by the piezoelectric transducer when the capillary contacts a solid surface, sends a signal to the motor control module to stop movement of the capillary. If no voltage excursion is detected, then the tip detection system signals the motor control module to continue its normal routine.

The diagram, omitting the tip detection system, illustrates the general operation of the microdrop dispensing apparatus. A capillary (or more typically multiple capillaries) is moved to a predetermined position and one or more drops are dispensed by applying a relatively high voltage to the piezoelectric transducer surrounding the capillary. Then, the capillary is moved to the next predetermined location by the positioning system as directed by the motor control module, which is instructed by the computer which controls the overall operation of the apparatus. The computer directs application of dispensing voltage to the capillary and also inactivates the tip detection system when voltage is to be applied to the transducer or at other times, such as when aspirating liquids or cleaning the capillaries.

The above discussion relates to a method in which the voltage created when a capillary contacts a solid surface is distinguished from random “noise” and used to stop the relative movement of the capillary and a sample plate or surface with which the capillary is being used. Alternatively, the invention also includes a method in which the capillary is pulsed at its resonant frequency with a voltage which does not

cause droplets to be expelled. An inverted phase is provided as a reference signal so that the two frequencies are in phase. When the capillary contacts a surface; the resonant frequency is shifted in phase from the inverted resonant frequency. By measuring the phase change relative to the inverted signal used as a reference, a signal
5 is sent to the motor control module of Figure 5 to stop further movement.

The resonant frequency may be determined for each capillary by increasing the frequency of the applied voltage until the resonant frequency is reached. Then, in a preferred embodiment, an inverted signal at the resonant conditions for the capillary is created as a reference. The two are in phase with each other as long as the capillary
10 is not touching a surface and is oscillating at its natural resonant frequency. However, when the capillary touches a surface, the oscillation of the capillary is no longer in phase with the inverted signal which had been created as a reference. Although the voltage change which results is small, the phase shift is large. One method of detecting this phase shift is to sum the reference signal with the signal from the
15 capillary. Usually, the sum of the signals cancel each other out and result in a zero voltage reading. When the phase of the capillary changes only slightly, the sum of the signals is no longer zero. The voltage change is read as being the result of the capillary touching a surface, then a signal to the motor control unit stops movement of the capillary, in a similar manner as that described for the first embodiment.

Detecting the Position of Surfaces

Although the invention has a particular value in preventing capillaries from being broken during operation of a microdrop dispensing apparatus, it can also be used to detect the position of surfaces. For example, in some applications it will be
25 necessary to position droplets precisely on the surface of a flat slide. Since the capillary tip will closely approach the surface before dispensing a droplet, it is important to know where the surface is. As noted earlier, the approach distance may be about 0.4 mm. Where multiple droplets are to be rapidly dispensed, each at a different location on a slide, knowing where the surface is positioned is important.
30 The invention can be used to locate the surface of a slide by the voltage change when contact is made or the voltage resulting from the phase shift compared to an inverted

reference as in the second embodiment. In this use, no further movement toward the surface would be made, but the motor control unit could be instructed to note the position of the surface for subsequent dispensing of droplets and to proceed with the regular dispensing program.

- 5 The same general method may be used to detect the position of a liquid surface, which might be liquid in a sample well or in a container from which liquid is to be aspirated. It is believed that the method of the second embodiment described above is especially useful in locating the position of liquid surfaces.

11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209
2210
2211
2212
2213
2214
2215
2216
2217
2218
2219